
# KHS Innocoll DP 1513





<sup>\*</sup>example illustration

## adhesives for labeling

- based on casein and dispersion
- ✓ for PET / PEN
- ✓ for labelling of difficult coated glass surfaces
- for paper labels
- easily removable in washmachine
- raw materials correspond to the FDA Directives 21 CFR 175. 105.

## product characteristics

The product is suitable for applying labels to plastic containers (e. g. PET, PEN) and additionally for labelling of difficult coated glass surfaces. Labelling with this adhesive can be easily removed in a automatic bottle washing machine under normal industrial conditions.

### application notes

The temperature processing range is 20 - 30 °C, ideal at 25 °C. Before a different adhesive is to be used on the machine, it must be cleaned carefully.

#### storage

The product can be stored in its original sealed container for at least 6 months at room temperature after date of production - but not below +4 °C.

characteristics	Innocoll DP 1513
viscosity, dyn.	60.000 ± 20.000 mPas
colour	beige-transparent
pH value	9,4 ± 0,2
density	$1,02 \pm 0,03 \text{ g/cm}3$

container	packing size	material number	
33 kg	18	134499010591	
1050 kg	1	301244607291	

To the best of our knowledge and experience, the data / information we have provided is reliable but it does not amount to a statement of assured properties in the context of the latest regulations issued by the Federal Court of Justice. With regard to the many options available in terms of alternative applications and operating conditions the data / information can only be regarded as of a non-binding nature. In each separate case it is necessary for you to carry out your own trials before large-scale use although, of course, in that respect our application technology is available to you upon request.