

KHS Innocoll DP 1513 PLUS



*example illustration

adhesives for labeling

- ✓ based on casein and dispersion
- ✓ for PET / PEN
- ✓ for labelling of difficult coated glass surfaces
- ✓ for paper labels
- ✓ easily removable in washmachine
- ✓ raw materials correspond to the FDA Directives 21 CFR 175.105.

product characteristics

The product is suitable for applying labels to plastic containers (e. g. PET, PEN) and additionally for labelling of difficult coated glass surfaces. Labelling with this adhesive can be easily removed in a automatic bottle washing machine under normal industrial conditions.

application notes

The temperature processing range is 20 - 30 °C, ideal at 25 °C. Before a different adhesive is to be used on the machine, it must be cleaned carefully.

storage

The product can be stored in its original sealed container for at least 6 months at room temperature after date of production - but not below +4 °C.

| characteristics | Innocoll DP 1513 PLUS |
|-----------------|-----------------------|
|-----------------|-----------------------|

| | |
|-----------------|--------------------|
| viscosity, dyn. | 70.000±25.000 mPas |
| colour | beige-transparent |
| pH value | 9,2 ± 0,2 |
| density | 1,02 ± 0,03 g/cm3 |

| container | packing size | material number |
|-----------|--------------|-----------------|
|-----------|--------------|-----------------|

| | | |
|---------|----|--------------|
| 33 kg | 18 | 134499010591 |
| 1050 kg | 1 | 301244607291 |