



*example illustration

adhesives for labeling

- ✓ based on casein / protein
- ✓ for glass
- ✓ for paper / stanniol
- ✓ high initial tack
- ✓ good resistance to condensate water
- ✓ product is able for high speed machines

product characteristics

The product is suitable for applying labels to normal - and lightly - coated glass surfaces, e.g. in the beverage-, foodstuffs- and pharmaceutical industries etc. The product has a very high resistance to condensate water and has a high initial tack; can be easily removed in a automatic bottle washing machine under normal industrial conditions. The product can be used at low temperatures on high speed machines. It has a very high mileage with low coating weight. Suitable for foiling as for heavy metal labeling.

application notes

The temperature processing range is 15 - 32 °C, ideal at approx. 28 °C. Before a different adhesive is to be used on the machine, it must be carefully cleaned.

storage

The product can be stored in its original sealed container for at least 6 months at room temperature after date of production - but not below +4 °C.

characteristics	Innocoll KS 1102
-----------------	------------------

viscosity, dyn.	60.000 ± 15.000 mPas
colour	Yellowish
pH value	7,0 ± 0,3
density	1,02 ± 0,03 g/cm3

container	packing size	material number
-----------	--------------	-----------------

33 kg	18	301244607480
1050 kg	1	301244607481
30 kg	18	301244607560