



*example illustration

adhesives for labeling

- ✓ synthetic polymers
- ✓ for glass
- ✓ short setting time
- ✓ very good wet tack
- ✓ good resistance to ice water
- ✓ good resistance to condensate water

product characteristics

The adhesive is suitable for labelling on treated and untreated glass bottle on modern labelling machines. The adhesive has a good resistance to ice- and condensate water, it has a very good wet tack, a fast setting time and a high adhesion.

application notes

The temperature processing range is 26 - 30 °C. Before a different adhesive is to be used on the machine, it must be carefully cleaned.

storage

The product can be stored in its original sealed container for at least 6 months at room temperature after date of production - but not below +4 °C.

characteristics Innocoll KS EW 122

viscosity, dyn.	ca. 120.000 mPas
colour	Yellowish
pH value	ca. 8,3 ±0,2
density	1,02 ± 0,03 g/cm ³

container packing size material number

32 kg	18	301244607530
1050 kg	1	301244607531
120 kg	4	301244607532
30 kg	18	301244607533
30 kg	18	301244607600

To the best of our knowledge and experience, the data / information we have provided is reliable but it does not amount to a statement of assured properties in the context of the latest regulations issued by the Federal Court of Justice. With regard to the many options available in terms of alternative applications and operating conditions the data / information can only be regarded as of a non-binding nature. In each separate case it is necessary for you to carry out your own trials before large-scale use although, of course, in that respect our application technology is available to you upon request.