



Future-proof labeling with the modular Innoket SE system.

Whether classic cold glue process, or hot glue labeling from sheets or rolls, or even contemporary no-label-look self-adhesive labels are used: The modular Innoket SE system can be changed over to different processes within next to no time. All labeling stations can very easily be docked on and off by using a lifting carriage.

The hot glue module

Less glue consumption thanks to nozzle application instead of roller application.

The roll-fed module

The non-slip label transport system makes for reliable operation.

The cold glue module

20,000 hours of operation until the next general overhaul.

The self-adhesive module

2 units mounted on a module provide for highest efficiency using automatically alternating operation.

The camera module

Bottle alignment only when needed.
Patented by KHS

Innoket SE options

- The Innoket ALM automatic label magazine with a storage capacity of up to 50,000 labels.
- Automatic label application from rolls using the roll-fed module's automatic splicer
- "ReDiS" – Remote Diagnostic Service and the AIS operating-data recording system provide for an optimal interaction between the Innoket SE, the filling line and the KHS service centers.

VarioDrive

The key to the Innoket SE system flexibility.

Rotating or pivoting movement, left side or right side application? Optimum programs for product

rotation are stored in the splash-proof VarioDrive control unit. In connection with the camera module for bottle alignment, embossed bottles in relief design will be individually rotated by the VarioDrive in such way that the label and the embossing are precisely aligned with each other and match.

Innoket SE

The new flexible solution in labeling that means you are well prepared for any changes in trends or market development

Entirely future-proof

Everything is possible: Cold glue, hot glue, self-adhesive, roll-fed application using paper or foil and tax strip application. Everything combined on one machine. And all options can be replaced, extended or adapted according to the design of your range of products at any time.



KHS GmbH

Juchostraße 20
D-44143 Dortmund
Phone: +49 (0) 231 / 5 69-1578
Fax: +49 (0) 231 / 5 69-1769
E-mail: michael.zwilling@khs.com
www.khs.com

